



FullHD Ultra Short Throw Projector

FEATURES

- Ultra Short-Throw 0.33:1 T.R.
- FullHD 1080p resolution
- Complete I/O connectivity incl. HDMI
- Direct 3D viewing via HDMI v.1.4
- 20W loudspeaker
- 5-year warranty, 3-year on lamp (or 2,000 hours, whichever comes first)
- Compatible with NovoConnect Wireless Presentation System for display
- Integrated 20W audio speakers
- Upon request, free of charge wall-mount bracket



Large image size revealing finest details in 1080p from an Ultra Short distance

The D758UST is the ultimate ultra-short-throw projector for the education that delivers a large 88" to 110" image from a ultra-short distance and enable perfect presentation without shadow obstruction and light glare in the presenter's eyes. The projector delivers a high brightness of 3,500 ANSI Lumens and an outstanding contrast ratio of 10,000:1 for a perfectly displayed image. The DH758UST projector can easily be mounted with the provided wall-mount bracket.



DH758UST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3500
	Native Resolution	1080p (1920x1080)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:9
	Contrast Ratio	10,000:1
	Keystone Correction	Vertical: +/- 40°
Optical	Throw Ratio	0.33: 1
	Zoom Ratio	Fixed 1x
	Image Size (Diagonal)	88" - 110"
	Projection Distance	341 - 510 mm
	Projection Lens	F = 2.5, f = 5.1 mm
	Offset (Based on Full Image Height)	124%
	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	Video SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)	
Connectivity	I/O Connection Ports VGA-In (15pin D-Sub) (x2), HDMI NA (x2: HDMI/MHLx1, HDMIx1), S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, USB A (Power Only), USB B (Service), Microphone (Mini-Jack)	
General	Dimensions (W x D x H)	287.7 x 374.5 x 122.6 mm (not including height of mirror)
	Weight	5
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 320W (Eco. Mode), 380W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	3,000 / 7,000 Hours (Normal / Eco. Mode), 280W/230W
	Speakers	10W x 2
	Noise Level	37dB / 33dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), IR interactive Pen / nbr, AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811119833-SVV), 3D Glasses P/N (3534257700), Universal Wall Mount (T/R 0.35) (3900228200), Remote Control P/N (5041827500), Interactive Pen P/N (5811118885-SVV)
	Warranty	Education Warranty: 5 years projector / 3 years on lamp or 2000 hours whichever comes first
	UPC Code	81309702024 6